



EXCELL SERIES 6000 **LIQUID POLYMER FEEDER**

The EXCELL Series 6000 Polymer Feeder provides the high energy needed to activate all types of liquid polymers.

The Series 6000 activates the polymer through a patented motor-less activation apparatus. It injects the polymer into the dilution water stream and immediately makes the solution flow through a low pressure, high energy, polymer activation nozzle.

SERIES 6000 MODELS

MODEL NUMBER	POLYMER FEED RATE GPD (LPH)	WATER FLOW RATE GPH (LPH)
6010A-X	0.1 to 10 GPD (0.02 to 1.6 LPH)	10 to 60 GPH (40 to 230 LPH)
6010A2-X	0.1 to 10 GPD (0.02 to 1.6 LPH)	10 to 120 GPH (40 to 460 LPH)
6024A2-X	0.6 to 24 GPD (0.1 to 3.8 LPH)	20 to 300 GPH (75 to 1140 LPH)
6010-X	0.1 to 10 GPD (0.02 to 1.6 LPH)	20 to 150 GPH (75 to 570 LPH)
6024-X	0.6 to 24 GPD (0.1 to 3.8 LPH)	30 to 300 GPH (115 to 1140 LPH)
6048-X	1.2 to 48 GPD (0.2 to 7.6 LPH)	30 to 300 GPH (115 to 1140 LPH)
6060-K	1.5 to 60 GPD (0.24 to 9.4 LPH)	60 to 600 GPH (230 to 2270 LPH)
6096-T	2.4 to 96 GPD (0.4 to 15 LPH)	120 to 1200 GPH (450 to 4500 LPH)
6108-T	3 to 108 GPD (0.5 to 17 LPH)	120 to 1200 GPH (450 to 4500 LPH)
6192-T	4 to 192 GPD (0.6 to 30 LPH)	120 to 1200 GPH (450 to 4500 LPH)
6240-T	5 to 240 GPD (0.6 to 38 LPH)	120 to 1200 GPH (450 to 4500 LPH)

TECHNICAL INFORMATION

- * The Series 6000 feeder has a solenoid operated diaphragm pump.
- * The Model 60XXA has a one gallon (4 liter) blending-aging tank.
- * The Model 60XXA2 has a one gallon (4 liter) blending-aging tank and post dilution water flow.
- * The feeders operate with potable or filtered process dilution water at 30 to 100 psi (2 to 6.9 Bar).
- * The water flow switch stops the polymer pump when the water flow drops below minimum.
- * The self-cleaning sight tube allows the operator to see how the feeder is operating. The patented assembly is operated by the polymer solution as it leaves the feeder.
- * The frame is made of welded stainless steel. Frame dimensions are: 16" x 18" x 24" tall.
- * The external injection valve is accessible without disturbing the activation apparatus. All components are modular and easy to access.
- * Operating voltage is 120 VAC. Power consumption is less than 5 Amps.

AVAILABLE OPTIONS

- * Peristaltic type polymer metering pump. See the Series 6000PS.
- * Progressive cavity type polymer metering pump. See the Series 6000PC.
- * Solenoid water valve. Option "J".
- * Dilution water flow capacity of 60 to 600 GPH (230 to 2270 L/H). Option "K".
- * Dilution water flow capacity of 120 to 1200 GPH (460 to 4500 L/H). Option "T".
- * Programmable pump, with digital display. It can accept a 4-20 mA signal. Option "S".
- * H-O-A Switch to allow remote start-stop control.
- * Timer to allow a flush cycle.
- * Pump speed controlled by the dilution water flow. This maintains solution concentration.
- * Contacts for remote indication of Alarm, Pump Run, or Auto Mode.
- * Low polymer flow alarm. The switch uses a thermal dispersion type sensor, with no moving parts. The trip point is adjustable down to 10 GPD (1.6 L/H).
- * In-line aging tank. Tanks have a polyethylene liner and are fiberglass reinforced. They are rated for 125 psi (8.5 Bar). No additional level controls or pumps are needed. Tank volumes of 20 to 350 gallons (75 to 1325 liter) are available.
- * Explosion proof for use in Class 1, Group D environments.
- * Voltages other than 120 VAC are available.
- * Dilution water pressure as high as 1500 psi (100 Bar).
- * Custom designed to meet your needs.